



US005941608A

United States Patent [19]
Campau et al.

[11] **Patent Number:** **5,941,608**
[45] **Date of Patent:** **Aug. 24, 1999**

1c971 U.S. PTO
09/939509
08/24/01

[54] **ELECTRONIC BRAKE MANAGEMENT SYSTEM WITH MANUAL FAIL SAFE**

FOREIGN PATENT DOCUMENTS

4413579 10/1995 Germany .

[75] Inventors: **Gregory P. Campau**, Plymouth, Mich.;
Andrew W. Kingston, Heidesheim, Germany; **Robert L. Ferger**, Homburg, Germany; **Thomas Welgert**, Bad Soden, Germany; **Salvatore Oliveri**, Filsen, Germany; **Blaise J. Ganzel**; **Mark S. Luckevich**, both of Ann Arbor, Mich.

OTHER PUBLICATIONS

"Electrohydraulic Brake System—The First Approach to Brake-By-Wire Technology" by Jonner et al., SAE Technical Paper Series #960991, copyright 1996 Society of Automotive Engineers, Inc.

[73] Assignee: **Kelsey-Hayes Company**, Livonia, Mich.

"Intelligent Braking for Current and Future Vehicles" by Schenk et al., SAE Technical Paper Series #950762, copyright 1995 Society of Automotive Engineers, Inc.

[21] Appl. No.: **08/813,146**

Primary Examiner—Chris Schwartz
Attorney, Agent, or Firm—MacMillan, Sobanski & Todd, LLC

[22] Filed: **Mar. 7, 1997**

Related U.S. Application Data

[57] **ABSTRACT**

[60] Provisional application No. 60/038,043, Mar. 6, 1997, provisional application No. 60/032,595, Dec. 2, 1996, provisional application No. 60/018,814, May 31, 1996, and provisional application No. 60/013,005, Mar. 7, 1996.

An improved electro-hydraulic brake system having features for improving the pedal feel of the system, while further having design features which contribute to the economy of manufacture of certain components of the system. The system provides for an electrically powered normal source of pressurized hydraulic brake fluid, and a manually powered backup source of pressurized hydraulic brake fluid to the vehicle brakes in the event of failure of the normal source. During normal braking, fluid from the backup source is redirected from the vehicle brakes to a pedal simulator. The pedal simulator preferably includes arrangements of spring loaded pistons, expansion volumes, and damping orifices, together with valves selectively controlling the flow of fluid to and from the pedal simulator which provides for an improved pedal feel during vehicle braking. The brake system of the invention further includes a relatively low cost fluid separator unit which is provided which prevents intermixing of pressurized fluid between the backup source and the normal source. The fluid separator unit acts to permit the normal source to act upon the hydraulic brake fluid of the backup source to operate the vehicle brakes. The fluid separator unit is preferably embodied as a piston having two working faces, each of the same diameter.

[51] **Int. Cl.⁶** **B60T 8/34**
[52] **U.S. Cl.** **303/113.4; 303/115.4; 303/84.2; 303/DIG 3**
[58] **Field of Search** 303/3, 10, 15, 303/113.4, 122.09, 122.11, 122.13, 155, 166, DIG. 3, DIG. 4, 115.1, 116.1, 115.4, 116.2, 84.2

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,462,642	7/1984	Leiber .	
4,812,777	3/1989	Shirai	303/14
5,123,713	6/1992	Steiner	303/100
5,230,549	7/1993	Osada et al. .	
5,261,730	11/1993	Steiner et al. .	
5,312,172	5/1994	Takeuchi .	
5,558,409	9/1996	Walenty et al. .	
5,567,021	10/1996	Gaillard .	
5,588,718	12/1996	Winner et al. .	
5,613,740	3/1997	Kawamoto et al. .	

20 Claims, 7 Drawing Sheets

